



ГИБРИДНАЯ ЭНЕРГИЯ

Deye

RESIDENTIAL ESS SOLUTION

DEYE SPRING RW SERIES

КУПИТЬ АККУМУЛЯТОР DEYE
WWW.DEYE-RUS.RU



Easy Operation & Maintenance

- Battery module auto networking (No DIP switches)
- Support remotely monitoring and upgrade the firmware via Deye inverter
- Support external power supply activation, prevents battery suspension
- Allow over-discharge direct recharge, easy to maintain.



Safer

- (LFP) Battery : Safe, long-lasting, high-efficiency. Built-in circuit breaker, Intelligent BMS. Eco-friendly materials, non-toxic, pollution-free module.



Flexible Application

- Support Max. 32 units in parallel
- Built-in 10A constant-current limit charge
- Compatible with any brand inverter charge and discharge
- Suited to provide energy for backup power, residential, etc.



Reliable

- Built-in circuit breaker, Support 200A charge and 240A discharge
- Charge from 0°C to 55°C, discharge from -20°C to 55°C

≥6000

Cycles

32 units

Max in parallel

70%

EOL

12kW

Maximum Output Power

Wall-Mounted Battery (LV)



Model		RW-G10.6		RW-F10.6	
Main Parameter					
Battery Chemistry		LiFePO ₄			
Built-in Circuit Breaker		125A 1P, 60Vdc		125A 2P, 60Vdc	
Capacity (Ah)		208			
Scalability		Max. 32 pcs pack (Max.340kWh) in parallel			
Nominal Voltage (V)		51.2			
Operating Voltage (V)		44.8 ~ 57.6			
Nominal Energy (kWh)		10.64			
Usable Energy (kWh) ^[1]		9.58			
Charge / Discharge	Max. Continuous	100 / 100		Charge : 200 / Discharge : 240	
Current (A) ^[2]	Peak	200 / 200 (10 sec)		300 (2mins)	
Other Parameter					
Recommend Depth of Discharge		90%			
Dimension (W × H × D, mm)		600 × 750 × 200 (Without hanging board)			
Weight Approximate (kg)		96kg		99kg	
Master LED Indicator		LED (SOC : 20% ~ SOC100% and working state)			
IP Rating of Enclosure		IP20			
Operating Temperature		Charge : 0 ~ 55°C / Discharge : -20°C ~ 55°C			
Recommend Operating Temperature		15°C ~ 35°C			
Storage Temperature		0°C ~ 35°C			
Relative Humidity		95% non-condensing			
Altitude		≤2000m			
Cycle Life		≥6000 (25°C±2°C, 0.5C / 0.5C, 90%DOD, 70%EOL)			
Installation		Wall-Mounted, Floor-Mounted			
Communication Port		CAN2.0, RS485			
Warranty Period ^[3]		5 years			
Energy Throughput		16MWh (25°C, 0.5C / 0.5C, 70%EOL)			
Certification		UN38.3, MSDS			

[1] Test conditions : 25°C±2°C, at beginning of life, 0.3C charge & 0.3C discharge,100% DOD.

[2] The current is affected by temperature and SOC.

[3] Conditions apply, refer to Deye Warranty Letter.